

(Set-L)

M.Tech - 1st
Fluid and Gas Dyna

Full Marks : 70

Time : 3 hours

Answer any six questions including Q. No. 1

The figures in the right-hand margin indicate marks

1. Answer the following questions : 2 × 10
- (a) Write the x-component of Euler's equation and explain the meaning of different terms.
- (b) Explain what you understand by flow work. What is the expression for it?
- (c) Explain the terms angular deformation and rotation. What is the relation between them?
- (d) Explain the difference between Stoke's law of viscosity and Newton's law of viscosity. Write down the equations in each case.

- (e) What is the Bernoulli's equation for flow of a compressible fluid?
- (f) What is a doublet? Draw its potential lines and stream lines.
- (g) Describe Kutta-Joukowski theorem with reference to flow around a cylinder.
- (h) Explain with the help of the relevant equation, how a nozzle in subsonic flow behaves like a diffuser in supersonic flow.
- (i) What is the use of the parameter $\Gamma/4\pi RU_0$ in determining the number of stagnation points in flow around a cylinder?
- (j) Explain with T-S diagram, the importance of Fanno and Rayleigh lines to determine the condition of a normal shock.
2. (a) Derive the equations for stagnation properties like T_0/T , P_0/P and ρ_0/ρ for an isentropic flow. 6

- (b) An object is immersed in an air flow with a

static pressure of 200 kPa(abs) and static temperature of 20°C and a velocity of 200 m/s. What are the temperature and pressure at the stagnation point? Take $R = 287 \text{ J/kgK}^\circ$. 4

3. (a) Show the pressure distribution along a converging and diverging nozzle for different values of back pressure. 5
- (b) A nozzle of throat area 2.5 cm is fixed on the side of a tank. The air pressure and temperature within the tank are 844 kPa and 15°C. Determine the back pressure for maximum discharge. Also calculate the maximum discharge. 5
4. (a) Explain the procedure for drawing the Fanno and Rayleigh lines along with the governing equations. <http://www.odishastudy.com> 5
- (b) A normal shock wave exists in a 500 m/s stream of nitrogen with static temperature and pressure of -40°C and 70 kPa respectively. Calculate the mach number, pressure and temperature downstream of the wave. 5

Derive the equations of velocity components in radial and circumferential directions. 5

- (b) A long circular cylinder lies in an air stream having a velocity of 60 m/s. In addition, there is a flow around the cylinder with circulation of $-400 \text{ m}^2/\text{s}$ (Clockwise). Neglecting viscous and compressibility effects, determine : 5
- (i) Location of stagnation points
- (ii) Lift force per unit length of cylinder.
- Take density of air as 1.22 kg/m^3 and cylinder diameter 1.2 m.

<http://www.odishastudy.com>

Whatsapp @ 9300930012

Send your old paper & get 10/-

अपने पुराने पेपर्स भेजे और 10 रुपये पायें,

Paytm or Google Pay से